

FP

PLATINUM FLUKSO

82% PVC
18% PES



TFP5



TFP12



TFP22



TFP30



TFP36



TFP15


VG

GORGEOUS FLUKSO

100% PES FR / TREVIRA CS



TVG2153



TVG2158



TVG2148



TVG2118



TVG2126



TVG2111

RX

REMIX 2 KVADRAT

90% LANA VERGINE / NEW WOOL
10% NYLON



TRX123



TRX682




TRX173



TRX662



TRX743



TRX982

HE

HERO KVADRAT

96% LANA VERGINE / NEW WOOL
4% NYLON



THE211



THE141



THE791



THE541



THE991



THE381

ST

STEELCUT TRIO 3 KVADRAT

90% LANA VERGINE / NEW WOOL
10% NYLON



TST133



TST916




TST195



TST515



TST716




TST376

LN

PANAMA DANI

100% PELLI BOVINE EUROPEE
100% EUROPEAN COW HIDES



LN5506



LN5290



LN5300



LN5210



LN5320




LN5400

SS



SOLIDS & STRIPES SUNBRELLA

100% ACRILICO / 100% ACRYLIC



TSS5453





























TSS5476



TSS5420

**SPECIFICHE TESSUTI
/ FABRIC FEATURES**

<p>Platinum Flukso 650 g/mq / g/sqm 100.000 Martindale</p>	<p>Gorgeous Flukso 450 g/mq / g/sqm 100.000 Martindale</p>	<p>Remix 2 Kvadrat 415 g/mtl / g/lin.m 100.000 Martindale</p>	<p>Hero Kvadrat 580 g/mtl / g/lin.m 45.000 Martindale</p>
			
			
			
			
			
			
			

**Steelcut Trio 3
Kvadrat**
770 g/mtl / g/lin.m
100.000 Martindale

**Panama
Dani**
sp / thk 1,0-1,2 mm

**Solids & Stripes
Sunbrella**
260 g/mq / g/sqm



**resistenza allo strappo
/ tear resistance**
20 N I EN ISO 3377 -1

**resistenza del colore ai raggi UV
- outdoor 1000h
/ colour fastness UV - outdoor 1000h**
4-5 / ISO 105 B04



**resistenza alla flessione
/ flex resistance**



**nessuna rottura
in 50.000 cicli
/ no damage
in 50.000 cycles**
EN ISO 5402

