


FELT MELANGE




582




610



612



619




620



623



635




640




641




642




650



651



652




846




847



848




849



855



858




859

FELT MELANGE


New colours



296




298




297



293




294




295



292



289



300



299

FELT MELANGE

EN

Composition:	70% Wool, 25% Polyamide, 3% Acrylic, 2% Polyester
Maintenance:	Vacuum regularly or professional Dry-clean
Abrasion Resistance:	90.000 Martindale cycles
Flammability:	EN 1021 part 1&2 BS 5852-1: 1979

DE

Zusammensetzung:	70% Wolle, 25% Polyamid, 3% Akryl, 2% Polyester
Reinigung:	Regelmässig staubsaugen. Professionelle Trockenreinigung
Scheuerfestigkeit:	90.000 Martindale
Feuerschutz:	EN 1021 part 1&2 BS 5852-1: 1979

FR

Composition:	70% Laine, 25% Polyamide, 3% Acryl, 2% Polyester
Nettoyage:	Aspirer régulièrement. Nettoyage à sec professionnel
Résistance à l'abrasion:	90.000 cycles Martindale
Normes au feu:	EN 1021 source d'ignition 1&2 BS 5852-1: 1979

DK

Materiale:	70% Uld, 25% Polyamide, 3% Akryl, 2% Polyester
Rengøring:	Støvsug regelmæssigt eller professionel rengøring
Slidstyrke:	90.000 Martindale
Flammesikring:	EN 1021 part 1&2 BS 5852-1: 1979